

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

AMENDMENTS TO THE CLAIMS**IN THE CLAIMS:**

This Listing of Claims will replace all prior versions, and listings, of claims in the subject Patent Application:

Listing of Claims:

Claim 1 (Currently amended): An integrated circuit (IC) physical verification method comprising the steps of:

a. processing layout data describing positions of conductive material residing on layers of an IC including a drawn inductor having a spiral to produce recognition layer data representing a two-dimensional boundary shape of the spiral that is a composite of two-dimensional shapes of all conductive material forming the spiral; and

b. processing the recognition layer data to generate parameter data describing a shape of the spiral the shape being divided into a plurality of polygonal segments for separate processing relating thereto.

Claim 2 (Original): The method in accordance with claim 1 further comprising the step of:

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

c. processing the recognition layer data to determine whether the spiral has turns of uniform width.

Claim 3 (Original): The method in accordance with claim 1 further comprising the step of:

c. processing the recognition layer data to determine whether all bends in the spiral are of uniform bend angle.

Claim 4 (Currently amended): The method in accordance with claim 1 further comprising the step of:

d. processing the recognition layer data to identify a position of the spiral.

Claim 5 (Currently amended): The method in accordance with claim 1 wherein the parameter data indicates at least one of the following:

a length of the spiral; ;

a width of conductive material forming turns of the spiral; ; and

spacing between conductive material forming turns of ~~the forming~~ the spiral.

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

Claim 6 (Currently amended): The method in accordance with claim 1 wherein the parameter data indicates at least one of the following:

- a number of sides of the spiral; and
- a diameter of an area bounded by the spiral.

Claim 7 (Original): The method in accordance with claim 1 further comprising the step of:

- c. processing the recognition layer data to determine whether all bends in conductors forming the spiral are of uniform bend angle.

Claim 8 (Currently amended): An integrated circuit (IC) physical verification method comprising the steps of:

- a. processing layout data describing positions of conductive material residing on layers of an IC including a drawn inductor having a spiral to produce recognition layer data representing a two-dimensional boundary shape of the spiral that is a composite of two-dimensional shapes of all conductive material forming the spiral; and

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

b. processing the recognition layer data to generate parameter data
describing a shape of the spiral; ~~The method in accordance with claim 1~~

wherein the inductor is a center tap inductor including the spiral and a
center tap coupled to a central portion of the spiral; ;

wherein the layout data comprises first binary data corresponding to each
layer indicating positions of conductive material on the corresponding layer; ;

wherein the recognition layer data comprises second binary data generated
as a Boolean function of portions of the first binary data corresponding
respectively to layers upon which conductive material forming the spiral and the
center tap resides; ; and

wherein the second binary data ~~indicates~~ distinguishes positions of all
conductive material forming the spiral ~~and refrains from indicating~~ positions of
any conductive material forming the center tap.

Claim 9 (Currently amended): An integrated circuit (IC) physical
verification method comprising the steps of:

a. processing layout data describing positions of conductive material
residing on layers of an IC including a drawn inductor having a spiral to produce
recognition layer data representing a two-dimensional boundary shape of the spiral

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

that is a composite of two-dimensional shapes of all conductive material forming the spiral; and

b. processing the recognition layer data to generate parameter data describing a shape of the spiral; ~~The method in accordance with claim 1~~

wherein the inductor is a spiral inductor including the spiral and a spoke coupled to one end of the spiral; ;

wherein the layout data comprises first binary data corresponding to each layer indicating positions of conductive material on the corresponding layer; ;

wherein the recognition layer data comprises second binary data generated as a Boolean function of portions of the first binary data corresponding respectively to layers upon which conductive material forming the spiral and the spoke resides; ; and

wherein the second binary data ~~indicates~~ distinguishes positions of all conductive material forming the spiral and ~~refrains from indicating~~ positions of any conductive material forming the spoke.

Claim 10 (Currently amended): The method in accordance with claim 1 wherein the boundary shape includes a plurality of polygonal shapes representing shapes of conductive material forming the spiral, and wherein step b comprises the substeps of:

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

b1. processing the recognition layer data to identify each polygonal shape and to determine a length of each identified polygonal shape; and

b2. summing the computed lengths of the polygonal shapes to determine a length of the spiral.

Claim 11 (Original): The method in accordance with claim 1 wherein the boundary shape includes a plurality of polygonal shapes representing shapes of conductive material forming the spiral, and wherein step b comprises the substep of:

b1. processing the recognition layer data to identify each polygonal shape and to determine a width of each identified polygonal shape.

Claim 12 (Currently amended): The method in accordance with claim 1 further comprising the step of:

c. processing the recognition layer data boundary shape to generate a netlist representation of the drawn inductor.

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

Claim 13 (Original): The method in accordance with claim 12 wherein the netlist representation of the drawn inductor includes data describing physical characteristics of the inductor influencing its inductance.

Claim 14 (**Currently amended**): The method in accordance with claim 1 further comprising the steps of:

c. processing the recognition layer data to determine a position of the inductor within the layout based on a position of the boundary shape of its spiral indicated by the recognition layer data; ;

d. processing the recognition layer data to determine whether all bends in conductors forming the spiral are of uniform bend angle; ;

e. processing the layout data to determine whether conductive material residing on separate layers and forming portions of the spiral inductor are interconnected.

Claim 15 (**Currently amended**): The method in accordance with claim 14 further comprising the steps of:

f. processing the recognition layer data to determine parameters relating to a shape of the spiral influencing the spiral's inductance; ; and

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

g. processing the data representing the layout to generate a netlist description of the spiral inductor including the parameters determined at step f.

Claim 16 (Currently amended): Computer-readable media containing software which when read and executed by a computer causes the computer to carry out an integrated circuit (IC) physical verification method comprising the steps of:

a. processing layout data describing positions of conductive material residing on layers of an IC including a drawn inductor having a spiral to produce recognition layer data representing a two-dimensional boundary shape of the spiral that is a composite of two-dimensional shapes of all conductive material forming the spiral; ; and

b. processing the recognition layer data to generate parameter data describing a shape of the spiral the shape being divided into a plurality of polygonal segments for separate processing relating thereto.

Claim 17 (Original): The computer-readable media in accordance with claim 16 wherein the method further comprises the step of:

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

c. processing the recognition layer data to determine whether the spiral has turns of uniform width.

Claim 18 (Original): The computer-readable media in accordance with claim 16 wherein the method further comprises the step of:

c. processing the recognition layer data to determine whether all bends in the spiral are of uniform bend angle.

Claim 19 (Currently amended): The computer-readable media in accordance with claim 16 wherein the method further comprises the step of:

d. processing the recognition layer data to identify a position of the spiral.

Claim 20 (Currently amended): The computer-readable media in accordance with claim 16 wherein the parameter data indicates at least one of the following:

a length of the spiral; ;

a width of conductive material forming turns of the spiral; ; and

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

spacing between conductive material forming turns of ~~the forming~~ the spiral.

Claim 21 (**Currently amended**): The computer-readable media in accordance with claim 16 wherein the parameter data indicates at least one of the following:

- a number of sides of the spiral; and
- a diameter of an area bounded by the spiral.

Claim 22 (**Currently amended**): The computer-readable media in accordance with claim 16 wherein the method further comprises the step of:

- c. processing the recognition layer data to determine whether all bends in conductors forming the spiral are of uniform bend angle.

Claim 23 (**Currently amended**): Computer-readable media containing software which when read and executed by a computer causes the computer to carry out an integrated circuit (IC) physical verification method comprising the steps of:

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

a. processing layout data describing positions of conductive material residing on layers of an IC including a drawn inductor having a spiral to produce recognition layer data representing a two-dimensional boundary shape of the spiral that is a composite of two-dimensional shapes of all conductive material forming the spiral; and

b. processing the recognition layer data to generate parameter data describing a shape of the spiral; ~~The computer-readable media in accordance with claim 16~~

wherein the inductor is a center tap inductor including the spiral and a center tap coupled to a central portion of the spiral; ;

wherein the layout data comprises first binary data corresponding to each layer indicating positions of conductive material on the corresponding layer; ;

wherein the recognition layer data comprises second binary data generated as a Boolean function of portions of the first binary data corresponding respectively to layers upon which conductive material forming the spiral and the center tap resides; ; and

wherein the second binary data indicates positions of all conductive material forming the spiral and refrains from indicating positions of any conductive material forming the center tap for determining an area of overlap between the center tap and spiral.

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

Claim 24 (**Currently amended**): Computer-readable media containing software which when read and executed by a computer causes the computer to carry out an integrated circuit (IC) physical verification method comprising the steps of:

a. processing layout data describing positions of conductive material residing on layers of an IC including a drawn inductor having a spiral to produce recognition layer data representing a two-dimensional boundary shape of the spiral that is a composite of two-dimensional shapes of all conductive material forming the spiral; and

b. processing the recognition layer data to generate parameter data describing a shape of the spiral; ~~The computer-readable media in accordance with claim 16~~

wherein the inductor is a spiral inductor including the spiral and a spoke coupled to one end of the spiral; ;

wherein the layout data comprises first binary data corresponding to each layer indicating positions of conductive material on the corresponding layer; ;

wherein the recognition layer data comprises second binary data generated as a Boolean function of portions of the first binary data corresponding

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

respectively to layers upon which conductive material forming the spiral and the spoke resides, ; and

wherein the second binary data indicates positions of all conductive material forming the spiral and refrains from indicating positions of any conductive material forming the spoke for determining an area of overlap between the spoke and spiral.

Claim 25 (Currently amended): The computer-readable media in accordance with claim 16 wherein the boundary shape includes a plurality of polygonal shapes representing shapes of conductive material forming the spiral, and wherein step b comprises the substeps of:

b1. processing the recognition layer data to identify each polygonal shape and to determine a length of each identified polygonal shape, ; and

b2. summing the computed lengths of the polygonal shapes to determine a length of the spiral.

Claim 26 (Original): The computer-readable media in accordance with claim 16 wherein the boundary shape includes a plurality of polygonal shapes

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

representing shapes of conductive material forming the spiral, and wherein step b comprises the substep of:

b1. processing the recognition layer data to identify each polygonal shape and to determine a width of each identified polygonal shape.

Claim 27 (Original): The computer-readable media in accordance with claim 16 wherein the method further comprises the step of

c. processing the recognition layer data boundary shape to generate a netlist representation of the drawn inductor.

Claim 28 (Original): The computer-readable media in accordance with claim 27 wherein the netlist representation of the drawn inductor includes data describing physical characteristics of the inductor influencing its inductance.

Claim 29 (Currently amended): The computer-readable media in accordance with claim 16 wherein the method further comprises the steps of:

MR3529-9

Serial Number: 10/820,365

Response to Office Action Dated 5 May 2006

c. processing the recognition layer data to determine a position of the inductor within the layout based on a position of the boundary shape of its spiral indicated by the recognition layer data; ;

d. processing the recognition layer data to determine whether all bends in conductors forming the spiral are of uniform bend angle; ;

e. processing the layout data to determine whether conductive material residing on separate layers and forming portions of the spiral inductor are interconnected.

Claim 30 (Currently amended): The computer-readable media in accordance with claim 29 wherein the method further comprises the steps of:

f. processing the recognition layer data to determine parameters relating to a shape of the spiral influencing the spiral's inductance; ; and

g. processing the data representing the layout to generate a netlist description of the spiral inductor including the parameters determined at step f.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.